

ZO-AC Series

APEX 7kW

Built for the Japan Market

Designed specifically for Japan's residential and commercial charging applications with reliable long-term performance.





KEY FEATURES

- J1772 (PSE), single phase
- Compact design-easy carry & install
- RFID, Bluetooth, Wi-Fi and 4G optional wireless
- IP66, IK10, and -40°C to +65°C rated for rugged outdoor
- Multiple protections for safe use
- Wall-mounted or pedestal-mounted installation

PROTECTIONS

- Overvoltage
- Undervoltage
- Overcurrent
- Overheat
- Short-Circuit
- Leakage
- Lightning
- Emergency Stop

CERTIFICATIONS

CE | PEA | ANATEL | ROHS | ENERGY STAR | FCC | CSA | RCM

GENERAL INFORMATION

J1772（PSE）	IP66	Wall / Pedestal
CONNECTOR	PROTECTION RATING	MOUNTED

TECHNICAL SPECIFICATIONS

Input Voltage	Single Phase 165-265V
Rated Current	32A
Operating Frequency	50 / 60 Hz
Operating Altitude	≤4000m
Operating Humidity	5%-95% RH, Non-condensing
Operating Temperature	-40 ℃ to + 60 ℃
Storage Temperature	-40 ℃ to + 85 ℃
IP Rating	IP 66
Mechanical Life	≥10000 plug-in cycles
Functions	Bluetooth / RFID / WiFi / 4G for option
Protocol	OCPP 1.6J
Product Size	336mm × 240mm × 210mm
Product Weight	4.5 kg

Reach out to ZO POWER for a smarter way to charge.

- Custom Branding
- Customized UI
- Cloud Platform
- OCPP1.6 ready
- OTA Update
- 24 / 7 Technical support

EMAIL
info@zo-power.com

WEBSITE
www.zo-power.com